



product description:

designed for distribution system with voltage 400 V and with maximum current 16 A  
 for installation in environment with increased humidity, dust, chemical and corrosion resistance, in environments with increased risk of mechanical damage  
 universal sealing grommets for cables and pipes (Ø16, 25, 32, 40 mm)  
 to install on materials with fire classes E or F, use thermally insulating pad

material: PVC

color: light gray RAL 7035 / dark gray RAL 7012

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 650 °C

fire class for underlying material: A1-D

protection types: IP 54

weight: 640 g

meets the requirements: ČSN EN 60670-1, ČSN EN IEC 60670-1 ed. 2:21

storage: ČSN 64 0090

8118\_LA - sealing grommets, terminal plate and cover screws placed in the box, each box packed in shrink foil and labelled; 24 pcs of boxes stacked in a carton; color - dark gray RAL 7012

8118\_KA - sealing grommets, terminal plate and cover screws placed in the box, each box packed in shrink foil and labelled; 24 pcs of boxes stacked in a carton; color - light gray RAL 7035

accessories:

terminal plate S-96; SP-96  
 screwless terminal plates TYP015, TYP016, TYP017, TYP018  
 sealing grommet 1618